

SERIES 240 CUSTOM ACCORDION DOORS



Commercial to residential. Institutional to industrial. It's the industry leading accordion door.

No matter what space you need divided, chances are the Series 240 is the door to perfectly suit your needs. Combining the merits of durability and function with natural beauty, the Series 240 saves on floor and wall space. It also gives you choices like curvable track, locks, latches, and multiple meeting posts. Simply put, the Series 240 doesn't force the choice between an elegant door and flawless functionality.



SoundProof Accordion Door Series 240

The Nuts And Bolts Of Our Nuts And Bolts

Our exclusive steel hardware hinge system is designed to keep doors operating smoothly and lends fantastic strength and long-term durability. It also means the doors stay solidly in place while both open and closed.

Available Finishes

Natural hardwoods, woodgrain vinyls, solid vinyls, textured vinyls, custom paint finishes, custom stain finishes, high pressure decorative laminate finishes and applied murals.

Shipping Information

Schedule: Series 240 with factory standard finish, 2 weeks (over 250 lineal feet by quote). All doors with special finish (after signed approved acknowledgment received) 3 weeks.

Method of Shipment

Shipments to commercial addresses.

Additional charges apply for non-commercial delivery and predelivery notification. Contact Office for questions.

Door Hanging Weight Average

Series 240:

6'8" height— 10 lbs. per lineal foot 8'0" height— 12 lbs. per lineal foot 10'0" height— 15 lbs. per lineal foot 12'0" height— 18 lbs. per lineal foot

ADA Compatible



The Series 240 was tested for ADA compliance for opening load force per ADA/BOMA SEC 4.1311. Tests conducted by MEI Charlton, Inc., Portland, OR.

Architectural Specifications

soundproof accordion door shall be accordion-type with panels connected continuously along the top and bottom by a steel hardware hinge system. Individual hinges are riveted to those adjoining, and contain stops to maintain a uniform extended position. Extruded vinyl seals securely connect all adjoining panels top to bottom. Doors shall be suspended by nylon wheels from aluminum overhead track. All necessary hardware shall be included for normal installation.

How Soundproof Accordion Door Packaging Even Protects Your Reputation

Because our accordion doors are often the final piece of a project's puzzle, the last thing you need inhibiting your project's completion is a door arriving damaged. Knowing this, we individually carton doors that are up to 15' wide. Single doors over 15' wide are always wood crated, thus ensuring everything possible is done to have all pieces arrive undamaged.

The Soundproof Accordion Door Guarantee

All Soundproof accordion door are custom made to fit each opening & warranted against failure due to defective materials or workmanship





Employee-Owned

You're assured a precise level of workmanship, service and long-term value with each order because every Soundproof accordion door employee shares in the success of a job well done.

Series 240 Product Specifications

Complete Product Specifications:

Please Visit www.soundproofaccordiondoor.com

Panels: 4-1/4" wide by 1/4" thick. Vinyl-Lam or hardwood veneer faces.

Panel Connectors: Flexible vinyl, color-coordinated to panel selection.

Track: 1-1/8" x 1" aluminum, dark bronze, clear or gold finish. (Curvable option available)

Wheels: Nylon wheel on steel axle with ball bearings supplied as standard.

Lead Post: 3/4" x 2-3/4" aluminum, color-coordinated to panel connector.

Jamb Molding: 1" wide by 3/8" deep aluminum.

Latch: Deadlatch with thumbturn two-sides. (Keylocks or magnetic catch options available)

Handle: Molded PVC with finger recess.

Width: No limitation.

Height: Vinyl-Lam up to 12'-1". Hardwoods up to 10'-1".

Stacking Space: 1-1/4" per foot plus 2-3/4" for lead post.